

ITEM SKU#: 662187482354

Lineo Linear High Bay

INDUSTRIAL LIGHTING | LINEAR HIGH BAYS



FEATURES

- CCT & power selectable capability.
- Exceptional efficacy of up to 141 lm/W.
- Soft & uniform light output with high CRI.
- Dimming capable.
- Instant start with no flickering or humming.

APPLICATIONS

Large Warehouses, Manufacturing Facilities, Gymnasiums, Athletic Facilities, Workshops, Auditoriums, Airport Hangars

MOUNTING OPTIONS

- Pendant Mounting *(Kit Sold Separately)*
- Surface Mounting *(Kit Sold Separately)*

PRODUCT DETAILS

ELECTRICAL

| | |
|---------------------------------|-------------------------|
| Max Power | 159.5 W |
| Voltage | 120-277 V |
| Current | 0.64 A |
| Power Factor | 0.9 |
| Total Harmonic Distortion (THD) | 15% |
| Surge Protection | L/N-PE: 6 kV, L-N: 6 kV |

LIGHTING PERFORMANCE

| | |
|--------------------------------|---|
| Lumens | 11332 lm-15581.5 lm-19122.7 lm-22597 lm |
| Efficacy | 141.65 lm/W |
| Color Temperature (Selectable) | 4000 K-5000 K |
| Color Rendering (CRI) | 86 |
| R9 (Red Value) | 22 |
| R13 (Skin Tones) | 88-86 |
| Beam Angle | 90° |
| Light Distribution | Type I, Very Short |
| Dimmable Lighting Control | Continuous Dimming to 10% or Below |

*Lumen output may vary by $\pm 10\%$ depending on the chosen power and CCT combination.
*R13 value is calculated at 165 W.

ENVIRONMENT

| | |
|--------------------------------|------------------|
| Operating Temperature | -22 °F ~ +122 °F |
| Suitable Location | DAMP |
| Ingress Protection Rating (IP) | IP20 |

LIFESPAN

| | |
|----------------------|---|
| Average Life (Hours) | 50,000 |
| Warranty (Years) | 5 <i>(Extendable Up to 10 Years)</i> |

COMPONENTS

| | |
|------------------|---------------------------|
| LED Light Source | LUMILEDS 2835 |
| Driver | BECKY BQE160C-260-PVF-AUX |

CONSTRUCTION

| | |
|-----------------------|---------------|
| Housing | Iron |
| Cover Material / Lens | Polycarbonate |
| Diffuser | Frosted |
| Base / Power Supply | Hard Wired |
| Finish | White |

PART NUMBER & QUALIFICATIONS


| | |
|-----------------------|---|
| Ordering Part Number | IK-LHBL2-165W-40/50K-WH |
| Qualified Part Number | IK-LHBL2-165W-40/50K-D["EM" or blank][BR, WH, BL, GR, SL]["M", "DM", "DP" or blank] |
| SKU Number | 662187482354 |



Not all product variations listed on this page are DLC qualified. Visit <https://www.designlights.org/qpl> to confirm qualification.


DIMENSIONS AND WEIGHT

| | |
|----------------------|--------|
| Length (Inches) | 24.8" |
| Width (Inches) | 12.20" |
| Height (Inches) | 1.57" |
| Wire Length (Inches) | 72" |
| Net Weight (lbs) | 5.95 |



PACKAGING

| | |
|-------------------------|----------------------|
| Box Dimensions (Inches) | 26.77" x 13" x 2.56" |
| Box Weight (lbs) | 8.15 |
| Quantity Per Box | 1 |



SUPPORTING DOCUMENTS

| DOCUMENTS | DOCUMENT LINK |
|---|---------------------------------|
| Product Sheet | View / Download |
| IES Files | View / Download |
| LM79 Report | View / Download |
| LM80 Report | View / Download |
| Installation Instructions | View / Download |

ORDERING INFORMATION

| SKU NUMBER | DESCRIPTION | QUANTITY/BOX |
|--------------|---|--------------|
| 662187482354 | LINEO LHB: 159.5 W / 11332-15581.5-19122.7-22597 LM / 40-50 K / 120-277 V / WHITE | 1 |

ACCESSORIES

INCLUDED IN THE BOX

| SKU NUMBER | PRODUCT CODE | DESCRIPTION | DOCUMENT LINK |
|--------------|--------------|-------------------|---------------------------------|
| 662187486000 | IK-ACC-CHM | CHAIN MOUNT CABLE | View / Download |

SOLD SEPARATELY

| SKU NUMBER | PRODUCT CODE | DESCRIPTION | DOCUMENT LINK |
|--------------|---------------------|-------------------------|---------------------------------|
| 662187482361 | IK-LHBL2-PM | PENDANT MOUNTING KIT | View / Download |
| 662187482385 | IK-LHBL2-SM | SURFACE MOUNTING KIT | View / Download |
| 662187482392 | IK-ACC-LHBL2-2FT-WG | WIRE GUARD 2FT | View / Download |
| 662187482422 | IK-LHBL2-EMB-16W | LED EMERGENCY DRIVER | View / Download |
| 662187482309 | IK-HB01DMS-A | MICROWAVE MOTION SENSOR | View / Download |
| 662187482316 | IK-HB03-R | SENSOR REMOTE | View / Download |

*Choice of one accessory: Mounting Bracket (Pendant Mount or Surface Mount) is included with the order.

Contact your IKIO sales representative to buy replacement/additional Mounting Bracket.

NOTE: Other Options on Request/Customized: **Driver** (EM-Emergency Driver), **Finish** (BR-Bronze, BL-Black, GR-Gray, SL-Silver), M-Motion Sensor, DM-DC Motion Sensor, DP-DC PIR Sensor)