

ITEM SKU#: 662187487793

Nevo Vapor Tight Light (2')

INDUSTRIAL LIGHTING | VAPOR TIGHT LIGHTS

FEATURES

- Designed for energy efficiency, the luminaire is very durable, has a long lifespan, and offers great savings.
- Provides high efficacy and uniform lighting that enhances visual comfort and is also safe for the eyes.
- Comes with CCT and power select capability, allowing better control to the user.
- Instant start without the nuisance of flickering or humming.
- Dimming capable and can be used in wet locations (IP65 rating).

APPLICATIONS

Workshops, Warehouses, Parking Lots, Hallways

PRODUCT DETAILS

ELECTRICAL

| Power (Selectable) | 15 W-20 W-25 W | |
|---------------------------------|----------------------|--|
| Voltage | 120-277 V | |
| Current | 0.06 A-0.08 A-0.10 A | |
| Power Factor | ≥0.9 | |
| Total Harmonic Distortion (THD) | ≤20% | |
| Surge Protection | 2 kV | |
| | | |

LIGHTING PERFORMANCE

| Lumens | 2250 lm-3000 lm-3750 lm | |
|--------------------------------|-------------------------|--|
| Efficacy | 150 lm/W | |
| Color Temperature (Selectable) | 3000 K-4000 K-5000 K | |
| Color Rendering (CRI) | 80 | |
| R9 (Red Value) | 11-18-7 | |
| R13 (Skin Tones) | 86-87-84 | |
| Beam Angle | 120° | |
| Light Distribution | Type I, Very Short | |
| Dimmable Lighting Control | 0-10 V Dimming | |
| | | |

*The values R9 & R13 are calculated at 25 W.



| ENVIRONMENT | |
|--------------------------------|------------------|
| Operating Temperature | -22 °F ~ +113 °F |
| Suitable Location | WET |
| Ingress Protection Rating (IP) | IP65 |
| LIFESPAN | |
| Average Life (Hours) | 50,000 |
| Warranty (Years) | 5 |
| | |
| COMPONENTS | |
| LED Light Source | Lumileds SMD2835 |
| Driver | IKIO Internal |
| CONSTRUCTION | |
| Housing | Aluminum |
| Cover Material / Lens | Polycarbonate |
| Diffuser | Frosted |
| Power Supply | Hard Wired |
| Finish | Gray |
| | |

PART NUMBER & QUALIFICATIONS

| Ordering Part Number | IK-TPS1-25/20/15W2FTBTB1A2-GRD30/40/50 |
|-----------------------|--|
| Qualified Part Number | DLC (In-Process) |
| SKU Number | 662187487793 |





info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2024 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.




DIMENSIONS AND WEIGHT

| | | - |
|------------------|--------|---|
| Length (Inches) | 22.83" | |
| Width (Inches) | 3.46" | |
| Height (Inches) | 3.24" | |
| Net Weight (lbs) | 2.2 | |

PACKAGING

| Box Dimensions (Inches) | 26.77" x 8.86" x 7.09" | |
|-------------------------|------------------------|--|
| Box Weight (Ibs) | 14.96 | |
| Quantity Per Box | 4 | |



SUPPORTING DOCUMENTS

| DOCUMENTS | DOCUMENT LINK |
|---------------------------|-----------------|
| Product Sheet | View / Download |
| IES Files | View / Download |
| LM79 Report | View / Download |
| LM80 Report | View / Download |
| Installation Instructions | View / Download |

ORDERING INFORMATION

| SKU NUMBER | DESCRIPTION | QUANTITY/BOX |
|--------------|--|--------------|
| 662187487793 | NEVO VAPOR TIGHT LIGHT: 2FT / 15-20-25 W / 2250-3000-3750 LM / 30-40-50 K / 120-277 V / GRAY | 4 |

ACCESSORIES

SOLD SEPARATELY

| SKU NUMBER | PRODUCT CODE | DESCRIPTION | DOCUMENT LINK |
|--------------|---------------|----------------------|-----------------|
| 662187482835 | IK-ACC-8W-EMD | EMERGENCY LED DRIVER | View / Download |

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

Page | 2

© 2024 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.