

ITEM SKU#: 662187486079

Ove Emergency Mini Wall Pack

INDUSTRIAL LIGHTING | WALL PACKS

FEATURES

- Excellent efficacy supported by high lumen output and CRI, resulting in bright and uniform illumination.
- Its CC selectable feature allows flexibility in applications.
- Rugged die-cast aluminum housing and an efficient heat sink make it durable and ideal for outdoor use.
- Offers wide distribution and greater energy savings compared to traditional fixtures.
- · Surge-protected and suitable for wet locations (IP65 rated)
- Dimming capable (0-10 V) for enhanced lighting experience

APPLICATIONS

Building Facades, Entrances, Courtyards, Commercial Spaces, Industrial Areas, Retail and Hospitality Buildings, Landscape Lighting

PRODUCT DETAILS

ELECTRICAL

Power	13.4 W
Voltage	120-277 V
Current	0.05 A
Power Factor	0.9
Total Harmonic Distortion (THD)	15%
Surge Protection L/N-PE: 2.5 kV, L-N: 2.5 kV	

LIGHTING PERFORMANCE

Lumens	1740 lm	
Efficacy	130.34 lm/W	
Color Temperature (Selectable)	3500 K-4000 K-5000 K	
Color Rendering (CRI)	82	
R9 (Red Value)	4	
R13 (Skin Tones)	82-83-81	
Beam Angle	100°	
BUG Rating (Backlight, Uplight, and Glare)	B1-U3-G1	
Dimmable Lighting Control	Continuous Dimming to 10% or Below	

EMERGENCY BACKUP

Emergency Power	5 W
Time	90 Minutes
Lithium Battery	3.7 V, 2500 mAh

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2024 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.





ENVIRONMENT	
Operating Temperature	-40 °F ~ +113 °F
Suitable Location	WET
Ingress Protection Rating (IP)	IP65
Impact Protection Rating (IK)	IK08

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Lumileds SMD 2835
Driver	HBE HB-LPG015G-52

CONSTRUCTION

Housing	Die-Cast Aluminum
Cover Material	PC-LEV2200KL
Diffuser	Clear
Power Supply	Hard Wired
Finish	Bronze

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-EMWP-15WBDPDA1-BRPEM35/40/50
Qualified Part Number	IK-EMWP-15WBDPDA1-[BR, WH, BL,C or Blank]["P" or blank]["EM" or blank]35/40/50
SKU Number	662187486079

Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.







DIMENSIONS AND WEIGHT

Length (Inches)	6.53"
Width (Inches)	3.77"
Height (Inches)	10.47"
Net Weight (Ibs)	3.21

PACKAGING

Box Dimensions (Inches)	20.94" x 14.17" x 11.61"	
Box Weight (lbs)	37.47	
Quantity Per Box	10	





SUPPORTING DOCUMENTS

DOCUMENTS	DOCUMENT LINK
Product Sheet	View / Download
IES Files	View / Download
LM79 Report	View / Download
LM80 Report	View / Download
Installation Instructions	View / Download

ORDERING INFORMATION

SKU NUMBER	DESCRIPTION	QUANTITY/BOX
662187486079	OVE EMERGENCY MINI WP: 13.4 W / 1740 LM / 35-40-50 K / 120-277 V / BRONZE	10

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com



© 2024 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.