



ITEM SKU#: 662187549439

DelphiccT & Power Selectable Back-Lit

Panel Light 2' x 2'

CPS SERIES | PANEL LIGHTS

FEATURES

- . Higher energy cost savings over conventional lighting fixtures
- Back-lit for effective light distribution.
- CCT & Power selectable for greater light control and efficiency.
- Evenly distributed flicker-free light.
- . To be used for covered ceilings only.
- High CRI for crisp colors.

APPLICATIONS

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other residential and commercial applications.

MOUNTING OPTIONS

Surface Mount Kit Suspended Mount Kit

PRODUCT DETAILS

ELECTRICAL

| Power (Selectable) | 20 W-30 W-40 W |
|---------------------------------|----------------------|
| Voltage | 120-277 V |
| Current | 0.08 A-0.11 A-0.15 A |
| Power Factor | 0.961 |
| Total Harmonic Distortion (THD) | 10.4% |
| Surge Protection | 3 kV |

LIGHTING PERFORMANCE

| Lumens | 2769 lm-4012.2 lm-5275 lm |
|--|--|
| Efficacy | 133.74 lm/W |
| Color Temperature (CCT) | 3500 K-4000 K-5000 K |
| Color Rendering (CRI) | 85 |
| R9 (Red Value) | 14 |
| R13 (Skin Tones) | 86 |
| Beam Angle | 120° |
| Light Distribution | Type VS |
| BUG Rating (Backlight, Uplight, and Glare) | B2 - U1 - G1 |
| Dimmable Lighting Control | Continuous Dimming to 10% or below (0-10V) |



ENVIRONMENT

| Operating Temperature | -14 °F ~ +133 °F | |
|--------------------------------|------------------|--|
| Suitable Location | DAMP | |
| Ingress Protection Rating (IP) | IP40 | |

LIFESPAN

| Average Life (Hours) | 50,000 |
|----------------------|---|
| Warranty (Years) | 5 (10 Years Warranty Option Available) |

COMPONENTS

| LED Light Source | BRIDGELUX 2835 LEDS | |
|------------------|---------------------|--|
| Driver | XZ-P0WER | |

CONSTRUCTION

| Housing | Aluminum | |
|-----------------------|---------------|--|
| Cover Material / Lens | Polycarbonate | |
| Diffuser | Frosted | |
| Base / Power Supply | Hard Wired | |
| Finish | White | |

PART NUMBER & OUALIFICATIONS


| Ordering Part Number IK-BL22-40/30/20-3540 | | |
|--|-----------------------------|--|
| Qualified Part Number | IK-BL22-40/30/20-354050-YLY | |
| SKU Number | 662187549439 | |







DesignLights Consortium® (DLC) qualified product (Premium). Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.





Delphi cct & Power Selectable Back - Lit Panel Light 2' x 2'






DIMENSIONS AND WEIGHT

| Length | 23.7" |
|------------------|-------|
| Height | 1.8" |
| Width | 23.7" |
| Net Weight (lbs) | 5.95 |

PACKAGING

| PAGRAGING | |
|-------------------------|-------------------------|
| Box Dimensions (Inches) | 25.27" x 7.87" x 27.44" |
| Box Weight (lbs) | 28.1 |
| Quantity Per Box | 4 |



SUPPORTING DOCUMENTS

| Product Sheet | View / Download |
|---------------------------|-----------------|
| Installation Instructions | View / Download |
| IES Files | View / Download |
| LM79 Files | View / Download |
| LM80 Files | View / Download |

ORDERING INFORMATION (Qualified Part Number # IK-BL22-40/30/20-354050-YLY)

| ITEM | DESCRIPTION | CASE |
|--------------|--|------|
| 662187549439 | DELPHI BACK-LIT PANEL 2' x 2': 20 W-30 W-40 W / 3500 K-4000 K-5000 K / 120-277 V / DIMMABLE / WHITE / DLC | 1 |

ACCESSORIES (OPTIONAL)

| 662187558875 | EMERGENCY PACK FOR LED FIXTURE 10W/90 MIN/SPLIT TYPE/L AC | 1 |
|--------------|--|---|
| 662187528601 | EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L DC | 1 |
| 662187548487 | HD401S-CR: SMART OCCUPANCY SENSOR ON/OFF ONLY | 1 |
| 662187548043 | HD407V-CR: SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING | 1 |
| 662187477046 | HD05R - REMOTE CONTROL | 1 |
| 662187557700 | IK-OCCS-B, HD406VRH-D: MICROWAVE SMART CONTROLLER (BLACK SENSOR) | 1 |
| 662187558073 | IK-OCCS-R, HD03R: MICROWAVE SMART REMOTE CONTROL | 1 |

MOUNTING OPTIONS

| 662187559032 | SURFACE MOUNT KIT | 1 |
|--------------|---------------------|---|
| 662187477107 | SUSPENDED MOUNT KIT | 1 |