



ITEM SKU#: 662187528298

Delphi Linear Low Bay 2'

CPS SERIES | LINEAR LOW BAYS

FEATURES

- CCT & Power Selectable capabilities for greater light control.
- · Quick and easy Installation.
- High energy savings as compared to the conventional linear fluorescent fixtures.
- . Long-lasting finish.
- · Smooth and evenly distributed light output with no dark areas.
- Suitable for multiple application because of its low profile and CCT & Power selectable feature.

APPLICATIONS

Large warehouses, retail applications, commerical buildings, underground parking, walkways, mezzaine floor.

MOUNTING OPTIONS

Chain Mount Kit

PRODUCT DETAILS

ELECTRICAL

Power (Selectable)	15 W-18 W-22 W-25 W
Voltage	120-347 V
Current	0.08 A
Power Factor	0.9
Total Harmonic Distortion (THD)	15%
Surge Protection	3 kV

LIGHTING PERFORMANCE

Lumens	1905 lm-2286 lm-2794 lm-3175 lm
Efficacy	127 lm/W
Color Temperature (CCT)	3500 K-4000 K-5000 K
Color Rendering (CRI)	80
R9 (Red Value)	2
R13 (Skin Tones)	86
Beam Angle	120°
Light Distribution	N/A
BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G2
Dimmable Lighting Control	Continuous Dimming to 10% or Below



ENVIRONMENT

Operating Temperature $-14 ^{\circ}\text{F} \sim +140 ^{\circ}\text{F}$		
Suitable Location	DAMP	
Ingress Protection Rating (IP)	IP40	

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5 (+10 Years Warranty Ontion Available)

COMPONENTS

LED Light Source	SMD2835 Lumiled	
Driver	JUSIN LE25D1S-HA	

CONSTRUCTION

Housing	Aluminum	
Cover Material / Lens	Polycarbonate, Lens: Round (Stocked)	
Diffuser	Frosted	
Base / Power Supply	Hard Wired	
Finish	White	

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-SL02R-15/18/22/25W-35/40/50KLV-C
Qualified Part Number	IK-SL02R (15/18/22/25)W-?35/40/50? K[SV,LV]-[S?][C,P]
SKU Number	662187528298








DesignLights Consortium® (DLC) qualified product (Premium). Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/ QPL to confirm which versions are qualified.





DIMENSIONS AND WEIGHT

Length	23.89"
Height	2.56"
Width	2.62"
Net Weight (lbs)	9.1



PACKAGING

Box Dimensions (Inches)	25.4" x 6.3" x 6.3"	
Box Weight (lbs)	10.77	
Quantity Per Box	4	

SUPPORTING DOCUMENTS

Product Sheet	View / Download
Installation Instructions	View / Download
IES Files	View / Download
LM79 Files	View / Download
LM80 Files	View / Download

ORDERING INFORMATION (Qualified Part Number # IK-SLO2R (15/18/22/25)W-?35/40/50?K[SV,LV]-[S?][C,P])

ITEM	DESCRIPTION	CASE
662187528298	DELPHI LINEAR LOW BAY 2': 15 W-18 W-22 W-25 W / 3500 K-4000 K-5000 K / 100-277 V / DIMMABLE / DLC	1

ACCESSORIES (OPTIONAL)

662187558875	EMERGENCY PACK FOR LED FIXTURE 10 W/90 MIN/SPLIT TYPE/L AC	1
662187528601	EMERGENCY PACK FOR LED FIXTURE 18 W/90 MIN/SPLIT TYPE/L DC	1
662187548487	HD401S-CR: SMART OCCUPANCY SENSOR ON/OFF ONLY	1
662187548043	HD407V-CR: SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING	1
662187477046	HD05R - REMOTE CONTROL	1
662187528342	ROPE CHAIN- HANGING CABLE SETS	1
662187477121	WALL MOUNT FOR 2 FT LINEAR LOW BAY	1
662187476711	WIRE GAURDS WITH CLIPS - 2 FT COMPATIBLE WITH CPS SERIES LINEAR LOW BAYS	1
662187548456	4 W EMERGENCY DRIVER	1

MOUNTING OPTIONS

662187472546	CHAIN MOUNT KIT		1