

CPS Series

ITEM SKU#: 662187547008

Delphi® Wall Pack (Full Cutoff)

INDUSTRIAL LIGHTING | LED WALL PACKS



FEATURES

- CCT & power selectable capabilities.
- Excellent light output with even and wide distribution.
- Saves greater energy over the traditional lighting fixtures.
- Suitable for operation in low working temperature.
- Moisture & dust resistant.
- Durable die-cast aluminum housing.
- Rugged construction which makes it ideal for use in outdoor spaces.

APPLICATIONS

Building facades, commercial spaces, industrial areas, retail & hospitality buildings that demand long service life and low maintenance.

PRODUCT DETAILS

ELECTRICAL

Power (Selectable)	40 W-60 W-80 W-100 W
Voltage	120-347 V
Current	-A
Power Factor	≥ 0.90
Total Harmonic Distortion (THD)	--

LIGHTING PERFORMANCE

Lumens	5600 lm-8400 lm-11200 lm-14000 lm
Efficacy	140 lm/W
Color Temperature (CCT)	3000 K-4000 K-5000 K
Color Rendering (CRI)	>70
R9 (Red Value)	N/A
R13 (Skin Tones)	N/A
Beam Angle	0-90°
Light Distribution	--
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	0-10 V Dimming

ENVIRONMENT

Operating Temperature	-22 °F ~ +113 °F
Suitable Location	WET
Ingress Protection Rating (IP)	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5 (+5 Years Extended Warranty Option Available)

COMPONENTS

LED Light Source	--
Driver	--

CONSTRUCTION

Housing	Die Cast Aluminum
Diffuser	--
Base / Power Supply	Hard Wired
Finish	Black / Bronze Customize (Optional)

QUALIFICATIONS

Model Number	IK-WP10-0100
SKU Number	662187547008



