

CPS Series ITEM SKU#: 662187546995

Delphi Wall Pack (Semi Cutoff) INDUSTRIAL LIGHTING | WALL PACKS

FEATURES

- CCT & power selectable capabilities.
- Excellent light output with even and wide distribution.
- Saves greater energy over the traditional lighting fixtures.
- Suitable for operation in low working temperature.
- Moisture & dust resistant.
- Durable die-cast aluminum housing.
- Rugged construction which makes it ideal for use in outdoor spaces.

APPLICATIONS

Building facades, commercial spaces, industrial areas, retail & hospitality buildings that demand long service life and low maintenance.

PRODUCT DETAILS

ELECTRICAL

Power (Selectable)	75 W-100 W-120 W	
Voltage	120-277 V	
Current		
Power Factor	0.98	
Total Harmonic Distortion (THD)	16.61%	

LIGHTING PERFORMANCE

Lumens	9000 lm-12500 lm-15763 lm
Efficacy	126.52 lm/W
Color Temperature (CCT)	3000 K-4000 K-5000 K
Color Rendering (CRI)	70
R9 (Red Value)	-27
R13 (Skin Tones)	N/A
Beam Angle	360°
Light Distribution	
${\ensuremath{BUG}}$ Rating (<code>Backlight</code> , <code>Uplight</code> , and <code>Glare</code>)	B2 - U3 - G3
Dimmable Lighting Control	0-10 V Dimming



ENVIRONMENT

Operating Temperature	-13°F ~ +113°F	
Suitable Location	WET	
Ingress Protection Rating (IP)	IP65	

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5 (+5 Years Extended Warranty Option Available)

COMPONENTS

LED Light Source	
Driver	

CONSTRUCTION

Housing	Die Cast Aluminum	
Diffuser	Glass	
Base / Power Supply	Hard Wire	
Finish	Bronze	

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-WPB03M-120W-304050K-PC
Qualified Part Number IK-WPB03M-120W-304050K	
SKU Number 662187546995	

DesignLights Consortium[®] (DLC) qualified product (Premium). Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.


The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.






DIMENSIONS AND WEIGHT

Length	14.25"
Height	7.56"
Width	9.36"
Net Weight (lbs)	
PACKAGING	
Box Dimensions (Inches)	
Box Weight (Ibs)	
Quantity Per Box	1





SUPPORTING DOCUMENTS

Product Sheet	View / Download
Installation Instructions	View / Download
IES Files	On Request
LM79 Files	On Request
LM80 Files	On Request

ORDERING INFORMATION (Qualified Part Number # IK-WPB03M-120W-304050K-PC)

ITEM	DESCRIPTION	CASE
662187546995	DELPHI WALL PACK (SEMI CUTOFF): 75 W-100 W-120 W / 3000 K-4000 K-5000 K / 120-277 V / DIMMABLE / DLC	1

ACCESSORIES

662187548449	DC 12 V MICROWAVE MOTION SENSOR	1
662187548432	DC 12 V PHOTOCELL	1
662187548456	4 W EMERGENCY BATTERY BACK UP WITH CABLE	1
662187477671	SHORTING CAP	1

