

Delphi Linear Low Bay 2'

COMMERCIAL LIGHTING | LINEAR LOW BAYS

FEATURES

- CCT & power selectable capabilities for greater light control.
- Evenly-distributed, high-efficacy illumination with no dark areas.
- Long-lasting finish that adds to the aesthetics of the space.
- $\ensuremath{\cdot}$ Quick and easy installation with the surface mounting feature.
- Suitable for multiple application areas because of its low-profile design.
- High energy savings compared to conventional linear fluorescent fixtures.

APPLICATION AREAS

Industrial Areas, Warehouses, Garages, Workshops, Commercial Spaces

PRODUCT DETAILS

ELECTRICAL

Power (Selectable)	15 W-18 W-22 W-25 W
Voltage	120-347 V
Current	0.08 A
Power Factor	0.9
Total Harmonic Distortion (THD)	15%
Surge Protection	3 kV

LIGHTING PERFORMANCE

Lumens	1905 lm-2286 lm-2794 lm-3175 lm
Efficacy	127 lm/W
Color Temperature (Selectable)	3500 K-4000 K-5000 K
Color Rendering (CRI)	80
R9 (Red Value)	2
R13 (Skin Tones)	85
Beam Angle	120°
BUG Rating (Backlight, Uplight, and Glare)	B1-U3-G2
Dimmable Lighting Control	Continuous Dimming to 10% or Below



ENVIRONMENT

Operating Temperature	-14 °F ~ +140 °F
Suitable Location	DAMP
Ingress Protection Rating (IP)	IP40
LIFESPAN	
Average Life (Hours)	50,000
Warranty (Years)	5 (Extendable Up to 10 Years)

COMPONENTS

LED Light Source	SMD2835 Lumiled
Driver	JUSIN LE25D1S-HA


CONSTRUCTION

Housing	Aluminum
Cover Material / Lens	Polycarbonate Lens: Round (Stocked)
Diffuser	Frosted
Base / Power Supply	Hard Wired
Finish	White

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-SL02R-15/18/22/25W-35/40/50KLV-C	
Qualified Part Number	IK-SL02R (15/18/22/25)W-?35/40/50?K[SV,LV]-[S?][C,P]	
SKU Number	662187528298	

Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.



© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.





DIMENSIONS AND WEIGHT

Length (Inches)	23.89"
Width (Inches)	2.62"
Height (Inches)	2.56"
Net Weight (Ibs)	9.1
PACKAGING	
Box Dimensions (Inches)	25.4" x 6.3" x 6.3"
Box Weight (lbs)	10.77
Quantity Per Box	4



SUPPORTING DOCUMENTS

DOCUMENTS	DOCUMENT LINK
Product Sheet	View / Download
IES Files	View / Download
LM79 Report	View / Download
LM80 Report	View / Download
Installation Instructions	View / Download

ORDERING INFORMATION

SKU NUMBER	DESCRIPTION	QUANTITY/BOX
662187528298	DELPHI LLB 2': 15-18-22-25 W / 1905-2286-2794-3175 LM / 35-40-50 K / 120-347 V / WHITE / DLC	4

ACCESSORIES

INCLUDED IN THE BOX

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187528342	IK-SL02/4/8R-RC	ROPE CHAIN	View / Download

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187476711	IK-SL02R-WG-2	WIRE GUARD - 2 FT	View / Download
662187484235	IK-SL02/4/8R-LP	LINKING PLATE	View / Download
662187484242	IK-SL02/4/8R-JC	JUNCTION COVER	View / Download

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

