

Simplex Linear Low Bay COMMERCIAL LIGHTING | LINEAR LOW BAYS

N Bay V BAYS

FEATURES

- Smooth and evenly distributed light output.
- Suitable for multiple applications due to its low profile.
- Saves comparatively more energy than conventional linear fluorescent fixtures.
- Metal surfaces are painted, before fabrication, with high gloss baked white matte powder paint, for better and long-lasting finish.
- · Comes with a diffusing lens.

APPLICATIONS

Ideal for large warehouses, retail applications, commercial buildings and work areas.

MOUNTING OPTIONS

Wall Mounting Kit

PRODUCT DETAILS

ELECTRICAL

Power	60 W
Voltage	100-277 V
Current	0.67A
Power Factor	0.9
Total Harmonic Distortion (THD)	20%

LIGHTING PERFORMANCE

Lumens	8280 lm	
Efficacy	138 lm/W	
Color Temperature (CCT)	4000 K	
Color Rendering (CRI)	82.1	
R9 (Red Value)		
R13 (Skin Tones)		
Beam Angle	180°	
Light Distribution	Type II, Very Short	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U3 - G2	
Dimmable Lighting Control	0-10 V, Range 10% - 100%	



ENVIRONMENT

Operating Temperature	-4 °F ~ +122 °F
Suitable Location	INDOOR
Ingress Protection Rating (IP)	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5 (7 Years / 10 Years Warranty Option Available)

COMPONENTS

LED Light Source	Seoul 3528
Driver	Meanwell

CONSTRUCTION

Housing	Aluminum and Metal sheet	
Base / Power Supply	Hard Wire	
Finish	White	
Diffuser	Frosted	

PART NUMBER & QUALIFICATIONS

Ordering Part Number	Number IK-ST08-0060-40-J	
Qualified Part Number	Not Qualified Yet	
SKU Number	662187548524	








DIMENSIONS AND WEIGHT

Length	96"
Height	3.35"
Width	3.56"
Net Weight (lbs)	
Chain Length	
Wire Length	



DYCKYCING

TAUKAUINU	
Box Dimensions (Inches)	
Box Weight (lbs)	
Quantity Per Box	2

DESCRIPTION

SUPPORTING DOCUMENTS

Product Sheet	View / Download
Installation Instructions	View / Download
IES Files	View / Download
LM79 Files	On Request
LM80 Files	On Request

ORDERING INFORMATION

ITEM

I I E IVI	DEGORII IION	OAGL
662187548524	SIMPLEX LINEAR LOW BAY: 8 FT / 60 W / 4000 K / 100-277 V / DIMMABLE / WHITE	
ACCESSORIES		
662187558875	EMERGENCY PACK FOR LED FIXTURE 10 W / 90 MIN/SPLIT TYPE/L AC	1
662187528601	EMERGENCY PACK FOR LED FIXTURE 18 W / 90 MIN/SPLIT TYPE/L DC	1
662187548487	HD401S-CR: SMART OCCUPANCY SENSOR ON/OFF ONL	1
662187477046	HD05R - REMOTE CONTROL	1
662187476728	AIRCRAFT CABLE	1
662187548043	HD407V-CR: SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING	1

MOUNTING OPTIONS

662187476636	WALL MOUNTING KIT	1

CASE