

ITEM SKU#: 662187486789

# **Aimant**

# Magnetic Retrofit Strip Kit

COMMERCIAL LIGHTING | MAGNETIC STRIPS



- Ready-to-install strip light that comes with magnetic retrofit technology, making upgrading traditional fixtures super convenient and time saving.
- Comes with wide aluminum carrier angles that provide improved heat dissipation and superb optic diffusion.
- With high lumen output and CRI, it provides bright, clear lighting with no flickering or noise.
- Its sleek, architectural grade design, sturdy exterior, and a fine-quality Meanwell driver ensure longevity and durability.
- The strip kit allows dimming (0-10 V) for better control.

### **APPLICATIONS**

For Direct Installation and Retrofitting of Traditional Lights in Existing Fixtures in Schools Offices, Hospitals, Hotels, Restaurants, Factories, Other Commercial Areas

### **PRODUCT DETAILS**

#### **ELECTRICAL**

Number of Strip	2
Power	24 W
Voltage	120-277 V
Current	0.10 A
Power Factor	0.9
Total Harmonic Distortion (THD)	20%
Surge Protection	1 kV

#### LIGHTING PERFORMANCE

Lumens3120 lmEfficacy130 lm/WColor Temperature (CCT)4000 KColor Rendering (CRI)80R9 (Red Value)8R13 (Skin Tones)84Beam Angle120°Light DistributionT5Dimmable Lighting ControlContinuous Dimming to 10% or Below		
Color Temperature (CCT)         4000 K           Color Rendering (CRI)         80           R9 (Red Value)         8           R13 (Skin Tones)         84           Beam Angle         120°           Light Distribution         T5	Lumens	3120 lm
Color Rendering (CRI) 80  R9 (Red Value) 8  R13 (Skin Tones) 84  Beam Angle 120°  Light Distribution T5	Efficacy	130 lm/W
R9 (Red Value) 8  R13 (Skin Tones) 84  Beam Angle 120°  Light Distribution T5	Color Temperature (CCT)	4000 K
R13 (Skin Tones) 84  Beam Angle 120°  Light Distribution T5	Color Rendering (CRI)	80
Beam Angle 120° Light Distribution T5	R9 (Red Value)	8
Light Distribution T5	R13 (Skin Tones)	84
<u> </u>	Beam Angle	120°
Dimmable Lighting Control Continuous Dimming to 10% or Below	Light Distribution	T5
	Dimmable Lighting Control	Continuous Dimming to 10% or Below



#### **ENVIRONMENT**

Operating Temperature	-4 °F ~ +113 °F
Suitable Location	DAMP
Ingress Protection Rating (IP)	IP20

#### **LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	5

#### **COMPONENTS**

LED Light Source	Samsung - SPMWHX228MD5XXW0XX
Driver	Cupower XZ-SA40B-420105-080065-Y-B

#### CONSTRUCTION

Housing	Aluminum
Cover Material	PC
Diffuser	Frosted
Base / Power Supply	Hard Wired
Finish	White

#### PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-MS42-24W-40K[MS,BM,EM,BLANK]
Qualified Part Number	IK-MS42-24W-40K[MS,BM,EM,BLANK]
SKU Number	662187486789







 $Not all \ product \ variations \ listed \ on \ this \ page \ are \ DLC \ qualified. \ Visit \ https://www.designlights.org/qpl \ to \ confirm \ qualification.$ 




# Aimant Magnetic Retrofit Strip Kit



#### **DIMENSIONS AND WEIGHT**

Length (Inches)	45.59"
Width (Inches)	0.71"
Height (Inches)	0.47"
Net Weight (lbs)	1.15
PACKAGING	
Box Dimensions (Inches)	48.81" x 8.26" x 8.86"
Box Weight (lbs)	24.25
Quantity Per Box	20



# **SUPPORTING DOCUMENTS**

DOCUMENTS	DOCUMENT LINK
Product Sheet	View / Download
IES Files	View / Download
LM80 Report	View / Download
Installation Instructions	View / Download

# **ORDERING INFORMATION**

SKU NUMBER	DESCRIPTION	QUANTITY/BOX
662187486789	AIMANT MRSK: 4FT / 2 STRIP / 24 W / 3120 LM / 4000 K / 120-277 V / WHITE	20

# **ACCESSORIES**

#### **SOLD SEPARATELY**

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187482835	IK-ACC-8W-EMD	EMERGENCY LED DRIVER	View / Download
662187482682	IK-ACC-S-ANT9	BI LEVEL DAYLIGHT HARVESTING MICROWAVE MOTION SENSOR	View / Download
662187482651	IK-ACC-R-RC100	SENSOR REMOTE PROGRAMMER	View / Download