

ITEM SKU#: 662187475523

Contrila CCT & Power Selectable Edge-Lit

Panel Light 2'x2'

COMMERCIAL LIGHTING | PANEL LIGHTS

FEATURES

- Edge-lit low-profile design.
- · CCT and wattage selectable for enhanced light control.
- High-quality LGP for evenly distributed light.
- · Supports dimming.

APPLICATIONS

Ideal for retrofitting inefficient light fixtures in malls, hospitals, airports, offices, lobbies and other commercial applications.

MOUNTING OPTIONS

Surface Mount Kit Suspended Mount Klt


PRODUCT DETAILS

ELECTRICAL

| Power (Selectable) | 20 W-30 W-36 W-40 W |
|---------------------------------|---------------------|
| Voltage | 120-277 V |
| Current | 0.44 A |
| Power Factor | ≥0.90 |
| Total Harmonic Distortion (THD) | 15% |

LIGHTING PERFORMANCE

| Lumens | 2500 lm-3750 lm-4500 lm-5000 lm |
|--|---------------------------------|
| Efficacy | 125 lm/W |
| Color Temperature (CCT) | 3000 K-3500 K-4000 K-5000 K |
| Color Rendering (CRI) | 80+ |
| R9 (Red Value) | 3-10-3 |
| R13 (Skin Tones) | |
| Beam Angle | 120° |
| Light Distribution | Type VS |
| BUG Rating (Backlight, Uplight, and Glare) | B2 - U2 - G1 |
| Dimmable Lighting Control | 0-10 V, Range 10% - 100% |



ENVIRONMENT

| Operating Temperature | -4 °F ~ +113 °F |
|--------------------------------|-----------------|
| Suitable Location | DAMP |
| Ingress Protection Rating (IP) | IP40 |

LIFESPAN

| Average Life (Hours) | 50,000 |
|----------------------|---|
| Warranty (Years) | 5 (10 Years Warranty Option Available) |

COMPONENTS

| LED Light Source | Epistar |
|------------------|---------|
| Driver | Lifud |

CONSTRUCTION

| Housing | Aluminum and High Quality LGP | |
|---------------------|-------------------------------|--|
| Diffuser | | |
| Base / Power Supply | Hard Wired | |
| Finish | White | |

PART NUMBER & QUALIFICATIONS

| Ordering Part Number | IK-FP22-0040-DY-XX-J |
|-----------------------|----------------------|
| Qualified Part Number | Not Qualified Yet |
| SKU Number | 662187475523 |





Contrila CCT & Power Selectable Edge-Lit Panel Light 2' x 2'


1





DIMENSIONS AND WEIGHT

| Lenght | 23.74" |
|-------------------------|--------|
| Height | 0.39" |
| Width | 23.74" |
| Net Weight (lbs) | |
| Chain Length | |
| Wire Length | |
| PACKAGING | |
| Box Dimensions (Inches) | |
| Box Weight (lbs) | |



SUPPORTING DOCUMENTS

Quantity Per Box

| Product Sheet | View / Download |
|---------------------------|-----------------|
| Installation Instructions | On Request |
| IES Files | On Request |
| LM79 Files | On Request |
| LM80 Files | On Request |

ORDERING INFORMATION

| ITEM | DESCRIPTION | CASE |
|--------------|--|------|
| 662187475523 | CONTRILA 2' x 2': 20 W-30 W-36 W-40 W / 3000 K-3500 K-4000 K-5000 K / 120-277 V / DIMMABLE / WHITE | 1 |

ACCESSORIES

| 662187558875 | EMERGENCY PACK FOR LED FIXTURE 10 W/90 MIN/SPLIT TYPE/L AC | 1 |
|--------------|--|---|
| 662187528601 | EMERGENCY PACK FOR LED FIXTURE 18 W/90 MIN/SPLIT TYPE/L DC | 1 |
| 662187548487 | SMART OCCUPANCY SENSOR ON/OFF ONLY | 1 |
| 662187548043 | SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING | 1 |
| 662187477046 | REMOTE CONTROL | 1 |

MOUNTING OPTIONS

| 662187477107 | SURFACE MOUNT KIT | 1 |
|--------------|---------------------|---|
| 662187476612 | SUSPENDED MOUNT KIT | 1 |