



# Defenza Tri-Proof Luminaire

# COMMERCIAL LIGHTING | TRI-PROOF LIGHTS



# **FEATURES**

- Rugged design to resist vandalism damages.
- Multiple CCT variants.
- Special design for multiple fixture linking.
- Designed for effective heat management.
- Dust & water resistant.

# **APPLICATIONS**

Underground Parking Lots, Metro Stations, Airports, Shools, Subway Stations, Stairwells, Tunnels, Hallways, Outdoor Playgrounds, Indoor Stadiums

# **PRODUCT DETAILS**

# **ELECTRICAL**

Power	40 W
Voltage	120-277 V
Current	0.37 A
Power Factor	≥0.90
Total Harmonic Distortion (THD)	

# LIGHTING PERFORMANCE

LIGHTING PERFORMANCE	
Lumens	5200 lm
Efficacy	130 lm/W
Color Temperature (CCT)	5000 K
Color Rendering (CRI)	80+
R9 (Red Value)	N/A
R13 (Skin Tones)	N/A
Beam Angle	120°
Light Distribution	
BUG Rating ( Backlight, Uplight, and Glare )	
Dimmable Lighting Control	Continuous Dimming to 10% or Below (0-10 V)

#### **ENVIRONMENT**

Operating Temperature	-10 °F ~ + 200 °F	
Suitable Location	WET	
Ingress Protection Rating (IP)	IP66	
Impact Protection (IK)	IK10	

#### **LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	<b>5</b> (10 Years Warranty Option Available)

#### **COMPONENTS**

LED Light Source	
Driver	

# **CONSTRUCTION**

Housing	Aluminum and Polycarbonate	
Diffuser	Frosted	
Base / Power Supply	Direct Wire	
Finish	White	

# **QUALIFICATIONS**

Model Number	Not Qualified Yet	
SKU Number	662187464275	








Technical Data Shee




# **DIMENSIONS AND WEIGHT**

Length	35.43"
Height	2.44"
Width	3.54"
Net Weight (lbs)	



# **PACKAGING**

Box Dimensions (Inches)	41.9" x 10.23" x 8.66"
Box Weight (lbs)	
Quantity Per Box	6



# **SUPPORTING DOCUMENTS**

Product Sheet	View / Download
Installation Instructions	View / Download
IES Files	View / Download
LM79 Files	View / Download
LM80 Files	On Request

# **ORDERING INFORMATION**

ITEM	DESCRIPTION	CASE
662187464275	DEFENZA TRI-PROOF LUMINAIRE: 4 FT / 40 W / 5000 K / 120-277 V / DIMMABLE / WHITE	1