

#### ITEM SKU#: 662187539553

# Dynamo 3 Stadium Flood Light

INDUSTRIAL LIGHTING | FLOOD LIGHTS

# **FEATURES**

- Superior aesthetics with a modern look.
- Excellent heat management system courtesy of multiple vents.
- 240° adjustable angle.
- Multi-faceted optic design to distribute light evenly and reduce glare.
- Resistant to electrical interference due to high quality chip.

# **APPLICATIONS**

Stadiums, Sports Fields, High Mast Lighting, Light Towers, or Ports.

# **PRODUCT DETAILS**

#### **ELECTRICAL**

| 495.9 W   |
|-----------|
| 277-480 V |
| 1.08 A    |
| 0.955     |
| 11.6%     |
| 10 kV     |
|           |

### LIGHTING PERFORMANCE

| Lumens                                       | 78265.6 lm                         |
|--|------------------------------------|
| Efficacy                                     | 157.8 lm/W                         |
| Color Temperature (CCT)                      | 5700 K                             |
| Color Rendering (CRI)                        | 73.3                               |
| R9 (Red Value)                               | -20                                |
| R13 (Skin Tones)                             | 73                                 |
| Beam Angle                                   | 30°                                |
| Light Distribution                           | Type I, Very Short                 |
| BUG Rating ( Backlight, Uplight, and Glare ) | B5-U3-G2                           |
| Dimmable Lighting Control                    | Continuous Dimming to 10% or Below |



### **ENVIRONMENT**

| Operating Temperature          | -22 °F ~ +122 °F  |
|--------------------------------|-------------------|
| Suitable Location              | WET               |
| Ingress Protection Rating (IP) | IP66              |
| Impact Protection Rating (IK)  | IK08              |
| LIFESPAN                       |                   |
| Average Life (Hours)           | 100,000           |
| Warranty (Years)               | 10                |
|                                |                   |
| COMPONENTS                     |                   |
| LED Light Source               | LUMILEDS          |
| Driver                         | INVENTRONICS      |
| CONSTRUCTION                   |                   |
| Housing                        | Die-cast aluminum |
| Cover Material / Lens          | PC                |
| Diffuser                       | Clear             |
| Base / Power Supply            | Hard Wire         |
| Finish                         | Black             |
| Effective Projected Area (EPA) | 1.59 ft²          |
| Wind Shear Rating              | 127.5 mph         |
|                                |                   |

## **PART NUMBER & QUALIFICATIONS**

LISTED

PREMIUM

| Ordering Part Number  | IK-SLEL2-0500-DV-57 (30D) |
|-----------------------|---------------------------|
| Qualified Part Number | IK-SLEL2-0500-DV-57       |
| SKU Number            | 662187539553              |
|                       | HS                        |

Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.

Note: \*Fixtures mustn't be mounted facing upwards; it won't be covered under warranty.



## info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2023 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.


The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

# ITEM SKU#: 662187539553 Technical Data Sheet Dynamo 3 Stadium Flood Light



#### **DIMENSIONS AND WEIGHT**

| Width (Inches)          | 16.33"                   |
|-------------------------|--------------------------|
| Height (Inches)         | 19.65"                   |
| Diameter (Inches)       | 15.94"                   |
| Net Weight (Ibs)        | 27.55                    |
| PACKAGING               |                          |
| Box Dimensions (Inches) | 17.71" x 17.71" x 13.97" |
| Box Weight (Ibs)        | 31.96                    |
| Quantity Per Box        | 1                        |
|                         |                          |



## SUPPORTING DOCUMENTS

| DOCUMENTS                 | DOCUMENT LINK   |
|---------------------------|-----------------|
| Product Sheet             | View / Download |
| IES Files                 | View / Download |
| LM79 Report               | View / Download |
| LM80 Report               | View / Download |
| Installation Instructions | View / Download |

# **ORDERING INFORMATION**

| SKU NUMBER   | DESCRIPTION  | QUANTITY/BOX |
|--------------|--|--------------|
| 662187539553 | DYNAMO 3 SFL : 495.9 W / 78265.6 LM / 5700 K / 277-480 V / BLACK / DLC | 1            |

## ACCESSORIES

## INCLUDED IN THE BOX

| SKU NUMBER   | PRODUCT CODE  | DESCRIPTION    | DOCUMENT LINK   |
|--------------|---------------|----------------|-----------------|
| 662187477060 | IK-ACC-SHIELD | SHIELD         | View / Download |
| 662187477213 | IK-ACC-YKMT   | YOKE MOUNT KIT | View / Download |

#### SOLD SEPARATELY

| SKU NUMBER   | PRODUCT CODE         | DESCRIPTION                      | DOCUMENT LINK   |
|--------------|----------------------|----------------------------------|-----------------|
| 662187477190 | IK-ACC-SFMB          | SLIP FITTER MOUNTING BRACKET     | View / Download |
| 662187478821 | IK-ACC-LAD           | LASER AIMING DEVICE              | View / Download |
| 662187479576 | IK-ACC- CNV-SNAP-AN0 | SYNAPSE- WIRELESS CONTROL SYSTEM | View / Download |

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2023 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

