

ITEM SKU#: 662187478005

Amplin Linear High Bay

INDUSTRIAL LIGHTING | HIGH BAYS

FEATURES

- Superior heat dissipation capability due to use of multiple heat sinks.
- Smooth and uniform light output with no flickering or humming.
- Sleek design and low-profile makes it suitable for a wide range of applications.
- Greater savings as compared to conventional fluorescent fixtures.
- Resistant to vibration and water.

APPLICATIONS

Manufacturing Facilities, Warehouses, Gymnasiums.

MOUNTING OPTIONS

- Suspended.
- Surface Mounted.

PRODUCT DETAILS

ELECTRICAL

Power	198.7 W
Voltage	100-277 V $*200$ V to 480 V Fixture Available.
Current	0.78 A
Power Factor	0.92
Total Harmonic Distortion (THD)	9.8%
Surge Protection	5 kV

LIGHTING PERFORMANCE

Lumens	29235 lm	
Efficacy	147.1 lm/W	
Color Temperature (CCT)	5000 K	
Color Rendering (CRI)	83	
R9 (Red Value)	6	
R13 (Skin Tones)	86	
Beam Angle	120°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B4-U2-G2	
Dimmable Lighting Control	0-10V Dimming	



ENVIRONMENT

Operating Temperature	-10 °F ~ +120 °F	
Suitable Location	DAMP	
Ingress Protection Rating (IP)	IP54	
LIFESPAN		
Average Life (Hours)	75,000	
Warranty (Years)	7	
COMPONENTS		
LED Light Source	Bridgelux 2835	
Driver	Moso	
CONSTRUCTION		
Housing	Aluminum	
Heat Sink	Aluminum	
Cover Material / Lens	Polycarbonate	
Diffuser	Frosted	
Base / Power Supply	Hard Wired	
Finish	White (Powder Coated)	

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-HBAX-0200-50-DY-RLV04BX
Qualified Part Number	IK-HBAX-0200-50-DY-RLV04BX
SKU Number	662187478005



Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.

RoHS

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.





DIMENSIONS AND WEIGHT

Length (Inches)	43.3"
Width (Inches)	9.86"
Height (Inches)	1.87"
Chain Length (Inches)	Adjustable Upto 72"
Wire Length (Inches)	11"
Net Weight (Ibs)	13.66
PACKAGING	
Box Dimensions (Inches)	45.07" x 3.93" x 12.20"
Box Weight (lbs)	16.15
Quantity Per Box	1



SUPPORTING DOCUMENTS

DOCUMENTS	DOCUMENT LINK
Product Sheet	View / Download
IES Files	View / Download
LM79 Report	View / Download
LM80 Report	View / Download
Installation Instructions	View / Download

ORDERING INFORMATION

SKU NUMBER	DESCRIPTION	QUANTITY/BOX
662187478005	AMPLIN LINEAR HIGH BAY : 198.7 W / 29235 LM / 5000 K / 100-277 V / WHITE	2

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187557700	IK-OCCS-B	IK-OCCS-B : HD406VRH-D: Microwave Smart Controller (Black Sensor)	View / Download
662187558097	IK-OCCS-W	IK-OCCS-W : HD406VRH-D: Microwave Smart Controller (White Sensor)	View / Download
662187558073	IK-OCCS-REMOTE	IK-OCCS-R: HD03R - Microwave Smart Remote	View / Download
662187479033	IK-EMH-18170-HY	EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L	View / Download
662187558875	IK-10W-ED	EMERGENCY PACK FOR LED FIXTURE 10W/90 MIN/SPLIT TYPE/L	View / Download

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

Page | 2

© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.