

ITEM SKU#: 662187547008

Delphi Wall Pack (Full cutoff)

INDUSTRIAL LIGHTING | WALL PACKS



FEATURES

- CCT & power selectable capabilities.
- Excellent light output with even and wide distribution.
- Saves greater energy over the traditional lighting fixtures.
- Suitable for operation in low working temperature.
- · Moisture & dust resistant.
- · Durable die-cast aluminum housing.
- Rugged construction which makes it ideal for use in outdoor spaces.

APPLICATIONS

Building facades, commercial spaces, industrial areas, retail & hospitality buildings that demand long service life and low maintenance.

PRODUCT DETAILS

ELECTRICAL

Power (Selectable)	40 W-60 W-80 W-100 W
Voltage	120-347 V
Current	0.30 A
Power Factor	0.967
Total Harmonic Distortion (THD)	11.29%
Surge Protection	2 kV

LIGHTING PERFORMANCE

Lumens	5600 lm-8400 lm-11200 lm-14000 lm
Efficacy	123.21 lm/W
Color Temperature (Selectable)	3000 K-4000 K- 5000 K
Color Rendering (CRI)	72.8
R9 (Red Value)	-33
R13 (Skin Tones)	74
Beam Angle	96.1°
Light Distribution	Type III - Very Short
BUG Rating (Backlight, Uplight, and Glare)	B1-U2-G1
Dimmable Lighting Control	Continuous Dimming to 10% or Below

ENVIRONMENT

Operating Temperature	-22 °F ~ +113 °F
Suitable Location	WET
Ingress Protection Rating (IP)	IP65
Impact Protection Rating (IK)	IK08

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Lumileds 3030
Driver	Weled Power

CONSTRUCTION

Housing	Die-cast Aluminum
Cover Material / Lens	Polycarbonate
Diffuser	Clear
Base / Power Supply	Hard Wire
Finish	Bronze

PART NUMBER & QUALIFICATIONS

Ordering Part Number	IK-WP10-0100[L;M]-[P;C;MC;PC;PSC;SC]-3CCT
Qualified Part Number	IK-WP10-0100[L;M]-[P;C;MC;PC;PSC;SC]-3CCT
SKU Number	662187547008







DesignLights Consortium® (DLC) qualified product (Premium). Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/ QPL to confirm which versions are qualified.





Delphi Wall Pack (Full cutoff)



DIMENSIONS AND WEIGHT

Length (Inches)	11"
Width (Inches)	9"
Height (Inches)	7"
Net Weight (lbs)	5.95
PACKAGING	
Box Dimensions (Inches)	12.2" x 8.46" x 10.83"
Box Weight (lbs)	7.05
Quantity Per Box	1





SUPPORTING DOCUMENTS

DOCUMENTS	DOCUMENT LINK
Product Sheet	View / Download
IES Files	View / Download
LM79 Report	View / Download
LM80 Report	View / Download
Installation Instructions	View / Download

ORDERING INFORMATION

SKU NUMBER	DESCRIPTION	QUANTITY/BOX
662187547008	DELPHI WP (FULL CUTOFF): 406080100W / 5600-8400-11200-14000LM / 304050K / 120-347 V / BRONZE / DLC	1

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187548449	IK-ACC-S-HD06VCRH-7B	DC12V MICROWAVE MOTION SENSOR	View / Download
662187548432	IK-ACC-PC-HD06VCRH-7A	PHOTOCELL AND DAYLIGHT HARVESTING SENSOR	View / Download
662187548456	IK-ACC-EM-FM04E-600400	4W EMERGENCY BATTERY BACK UP WITH CABLE	View / Download
662187482644	IK-ACC-HD406VCRH-7-ZR	RECEPTACLE	View / Download
662187477046	IK-ACC-HD05R	REMOTE FOR MICROWAVE MOTION SENSOR	View / Download