PRODUCT SHEET





PRODUCT DETAILS

IKIO's T8 Tube is an advanced version of the existing T8 Tube Type A&B, with CCT & Power selectable capabilities. This new all-in-one LED T8 Tube will provide multiple wattages and color temperatures in a single SKU while keeping intact its proficiency in delivering splendid light distribution and reducing undesirable glare.

FEATURES

- Incorporates CCT & power selectable capabilities.
- Exceptional light output with low energy and maintenance cost.
- Can be used with existing instant start ballasts.
- Complies with UL, FCC and DLC standards.
- **Dual Mode Internal Driver** (UL Type A&B) to best suit your needs.

APPLICATIONS

📱 🕍 🎰 🏷

Offices Hospitals Coridoors Schools Stairways Underground Stations

WARRANTY & QUALIFICATIONS



DesignLights Consortium[®] (DLC) Premium qualified product. Not all versions of this product may be DLC qualified. qualified.Please check the DLC Qualified Products List at <u>www.designlights.org</u>/ QPL to confirm which versions are qualified.

*Warranty and Qualifications can vary per item/SKU, see technical data sheets (TDS) for specific information.

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com

Page | 1

© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.



PRODUCT ORDERING DETAILS (QUALIFICATION MODEL # IK-T804)

100-277 V FIXTURES

POWER SELECTABLE RANGE	ITEM#	DESCRIPTION	DLC	FINISH	SIZE	CCT SELECTABLE RANGE	EFFICACY	LUMENS	AVG. LIFE HOURS	DIFFUSER	BASE	CASE
10 W-12 W -15 W	662187477800	DELPHI T8 TUBES: 10 W-12 W-15 W / 3500 K-4000 K-5000 K	*	WHITE	4 FT	3500 K-4000 K -5000 K	170 lm/W-150 lm/W -130 lm/W	1700 lm-1800 lm -1950 lm	50,000	CLEAR		1
10 W-12 W -15 W	662187547015	DELPHI T8 TUBES: 10 W-12 W-15 W / 3500 K-4000 K-5000 K	*	WHITE	4 FT	3500 K-4000 K -5000 K	170 lm/W-150 lm/W -130 lm/W	1700 lm-1800 lm -1950 lm	50,000	FROSTED		1

100-347 V FIXTURES

POWER SELECTABLE RANGE	ITEM#	DESCRIPTION	DLC	FINISH	SIZE	CCT SELECTABLE RANGE	EFFICACY	LUMENS	AVG. LIFE HOURS	DIFFUSER	BASE	CASE
10 W-12 W -15 W	662187477817	DELPHI T8 TUBES: 10 W-12 W-15 W / 3500 K-4000 K-5000 K	*	WHITE	4 FT	3500 K-4000 K -5000 K	170 lm/W-150 lm/W -130 lm/W	1700 lm-1800 lm -1950 lm	50,000	CLEAR		1
10 W-12 W -15 W	662187477824	DELPHI T8 TUBES: 10 W-12 W-15 W / 3500 K-4000 K-5000 K	*	WHITE	4 FT	3500 K-4000 K - 5000 K	170 lm/W-150 lm/W - 130 lm/W	1700 lm-1800 lm -1950 lm	50,000	FROSTED		1

info@ikioledlighting.com | +1 844-533-4546 | www.ikioledlighting.com



© 2021 IKIO LED LIGHTING. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.