



Shenzhen Belling Efficiency Testing Lab



Report No.:BL180517007-9

Date of issue 2018-05-18

Version 1.0

Total pages 15

Test report of

IES LM-79-08

Approved Method: Electrical and Photometric

Measurements of Solid-State Lighting Products

Applicant:

IKIO LED LIGHTING

Address:

8470 Allison Pointe Blvd, Suite 128 Indianapolis, IN 46250

For Product:

Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

Model No.:

IK-SBSL2-L130-0150A-3000K / IK-SBSL2-L130-0150A-5700K

Test laboratory: Shenzhen Belling Efficiency Testing Lab., 1/F., Building 1, 1F, No.1 building, Meibaohe industrial park, Dalang street, Shenzhen, Guangdong Prov.518101, China.

Complied by: Zac Kuang

Review by: Jason Zhou

Project Engineer

Technical Manager

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or use in part without prior written consent from Shenzhen Belling Efficiency Testing Lab. This report must not be used by the customer to claim product certification, approval, or endorsement By NVLAP, NIST, or any agency of the U.S. Government.



1 General

1.1 Product Information

Manufacturer	IKIO LED LIGHTING
Manufacturer Address	8470 Allison Pointe Blvd, Suite 128 Indianapolis, IN 46250
Brand Name	IKIO
Luminaire Type	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Model Number	IK-SBSL2-L130-0150A-3000K / IK-SBSL2-L130-0150A-5700K
Rated Inputs	AC 120-277V 50/60Hz
Rated Power	150 W
Nominal CCT	3000K / 5700K
Date of Receipt Samples	2018-05-14
Date of Test	2018-05-14 to 2018-05-17

1.2 Standards or methods

- ANSI C78.377-2015: Specifications for the Chromaticity of Solid State Lighting Products
- ANSI C82.77-2002: Harmonic Emission Limits-Related Power Quality Requirements for Lighting Equipment
- CIE Publication No.13.3-1995: Method of Measuring and Specifying Color Rendering of Light Sources
- IESNA LM-79-08 Approved Method: Electric & Photometric Measurement of Solid-state Lighting Products



1.3 Equipment list

Device	Manufacture	Model No.	Serial No.	Calibration due date
Goniophotometric System	SENSING	GMS-3000	N.A	2018-09-20
AC Power Source	ALL POWER	APW-110N	992257	2018-08-26
Total Luminous Flux Standard Lamp	SENSING	110V/100W	S13100234	2018-09-14
Digital Power Meter	YOKOGAWA	WT310	C2QM02030V	2018-08-28
Integral Sphere	SENSING	SPR-600M	N.A	2018-08-26
Digital Power Meter	YOKOGAWA	WT210	91L929742	2018-08-28
Optical Color and Electrical Measurement System	SENSING	SPR-3000	N.A	2018-08-26
Temperature/humidity/clock	VICTOR	VC230	57636	2018-09-12
Digital Anemometer	TECMAN	TD8901	026141	2018-09-12

Statement of Traceability: Shenzhen Belling Efficiency Testing Lab attests that all calibration has been performed using suitable standards traceable to national primary standards and International System of Unit (SI).



2 Test conducted and method

2.1 Ambient Condition

The ambient temperature in which measurements are being taken was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, the air flow around the sample(s) being tested did not affect the performance.

2.2 Power Supply Characteristics

The AC power supply had a sinusoidal voltage wave shape at the prescribed frequency (60 Hz) such that the RMS summation of the harmonic components does not exceed 3 percent of the fundamental during operation of the test item.

The voltage of AC power supply (RMS voltage) applied to the device under test was regulated to within ± 0.2 percent under load.

2.3 Seasoning and Stabilization

No seasoning was performed in accordance with IESNA LM-79-08. And before the measurement, the sample was stabilized until the light output and power variations were less than 0.5% in 30 minutes intervals (3 readings, 15 minutes apart).

2.4 Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, spectrophotometer, and integrating sphere. The integrating sphere system is calibrated by standard light source before measurement. The system and standard light source has been calibrated regularly and traceable to the National Primary Standards. 4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

2.5 Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement. The standard light source has been calibrated regularly and traceable to the National Primary Standards.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The method according to IESNA LM-79-08 following chapter.



3 Test Result Summary

3.1 Integrating Sphere System

3.1.1 Electrical data

Model Number	Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
IK-SBSL2-L130-0150A-3000K	120.03	60	1.304	155.74	0.995
IK-SBSL2-L130-0150A-5700K	120.00	60	1.282	153.09	0.995

3.1.2 Photometric data

Model Number	Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)	CRI	R9
IK-SBSL2-L130-0150A-3000K	20168.33	129.5	3002	83.8	12
IK-SBSL2-L130-0150A-5700K	22152.12	144.7	5668	84.3	17

3.1.3 Chromaticity Coordinate

Model Number	Duv	x	y	u'	v'
IK-SBSL2-L130-0150A-3000K	0.00106	0.4384	0.4073	0.2501	0.5228
IK-SBSL2-L130-0150A-5700K	0.00148	0.3287	0.3407	0.2045	0.4768

3.2 Goniophotometer System

3.2.1 Electrical data

Model Number	Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
IK-SBSL2-L130-0150A-3000K	120.08	60	1.2897	154.05	0.9947

3.2.2 Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	Zonal Lumen in 0-90°(%lm)	Zonal Lumen in 80-90°(%lm)
19930.88	129.38	99.824	1.049



3.3 Additional Test

Model Number	Test Item	Test Voltage (V)	Frequency(Hz)	Test Result
IK-SBSL2-L130-0150A-3000K	Power Factor	277	60	0.931
	THD	277	60	14.3%



4 Test Data

IK-SBSL2-L130-0150A-3000K

Test Condition


Temperature: 25°C

RH: 58%

Spectrum Range: 350-800 nm

Scan Step: 5 nm

Spectroradiometric Parameters

Chromaticity Coordinates: $x=0.4384$ $y=0.4073$ $u'=0.2501$ $v'=0.5228$

Correlated Color Temperature: 3002 K

Dominant Wavelength: 581.0 nm(E)

Colour Fidelity Index: $R_f=84$ Gamut Index: $R_g=95$

Luminous Flux: 20168.33 lm

Purity: 0.5401

Chromaticity Difference: $+0.00106Duv$

Peak Wavelength: 605.0 nm

Color Ratio: $K_r=44.8\%$ $K_g=47.8\%$ $K_b=7.5\%$

Bandwidth: 130.2nm

Radiant Flux: 51.531 W

Photosynthetically Active Radiation(PAR): 49.57W

Photosynthetic Photon Flux(PPF): 241.23 μ mol/sRendering Index: $R_a=83.8$ $R_1=82$ $R_2=92$ $R_3=97$ $R_4=82$ $R_5=82$ $R_6=90$ $R_7=84$ $R_8=61$ $R_9=12$ $R_{10}=81$ $R_{11}=82$ $R_{12}=72$ $R_{13}=85$ $R_{14}=99$ $R_{15}=75$ $R_e=78$

Electric Parameters

Voltage: 120.03 V

Current: 1.304 A

Power Factor: 0.995


Power: 155.74 W

Luminous Efficacy: 129.5 lm/W

**IK-SBSL2-L130-0150A-5700K****Test Condition**

Temperature: 25°C
Spectrum Range: 350-800 nm

RH: 58%
Scan Step: 5 nm

Spectroradiometric Parameters

Chromaticity Coordinates: $x=0.3287$ $y=0.3407$ $u'=0.2045$ $v'=0.4768$

Correlated Color Temperature: 5668 K

Dominant Wavelength: 514.0 nm(E)

Colour Fidelity Index: $R_f=80$

Gamut Index: $R_g=93$

Luminous Flux: 22152.12 lm

Purity: 0.0156

Chromaticity Difference: +0.00148Duv

Peak Wavelength: 455.0 nm

Color Ratio: $K_r=32.3\%$ $K_g=55.8\%$ $K_b=11.9\%$

Bandwidth: 21.3nm

Radiant Flux: 67.001 W

Photosynthetically Active Radiation(PAR): 64.72W

Photosynthetic Photon Flux(PPF): 296.32 μ mol/s

Rendering Index: $R_a=84.3$

$R_1=83$ $R_2=91$ $R_3=93$ $R_4=82$ $R_5=82$ $R_6=84$ $R_7=88$ $R_8=70$

$R_9=17$ $R_{10}=76$ $R_{11}=80$ $R_{12}=58$ $R_{13}=86$ $R_{14}=96$ $R_{15}=80$ $R_e=78$

Electric Parameters

Voltage: 120.00 V

Current: 1.282 A

Power Factor: 0.995

Power: 153.09 W

Luminous Efficacy: 144.7 lm/W

**Zonal Flux Diagram**


Zonal flux distribution table

$\gamma(^{\circ})$	Average I(cd)	Zonal F(lm)	Sum F(lm)	Eff Flux(%)	Eff Sum(%)
0.0	3976.934	.000	.000	.000%	.000%
5.0	4016.639	95.561	95.561	.479%	.479%
10.0	4107.335	290.620	386.181	1.458%	1.938%
15.0	4222.235	494.105	880.285	2.479%	4.417%
20.0	4361.067	707.385	1587.670	3.549%	7.966%
25.0	4520.568	931.520	2519.190	4.674%	12.640%
30.0	4681.564	1164.537	3683.727	5.843%	18.483%
35.0	4826.379	1400.111	5083.838	7.025%	25.507%
40.0	4882.946	1619.928	6703.766	8.128%	33.635%
45.0	4819.852	1796.552	8500.318	9.014%	42.649%
50.0	4687.140	1921.027	10421.340	9.638%	52.287%
55.0	4523.151	2002.624	12423.970	10.048%	62.335%
60.0	4124.835	1998.958	14422.930	10.029%	72.365%
65.0	3631.526	1885.586	16308.510	9.461%	81.825%
70.0	2955.913	1667.982	17976.500	8.369%	90.194%
75.0	1520.354	1170.024	19146.520	5.870%	96.065%
80.0	498.667	540.234	19686.750	2.711%	98.775%
85.0	125.466	169.592	19856.350	.851%	99.626%
90.0	18.425	39.398	19895.740	.198%	99.824%
95.0	3.454	5.991	19901.730	.030%	99.854%
100.0	3.332	1.844	19903.580	.009%	99.863%
105.0	3.604	1.856	19905.430	.009%	99.872%
110.0	4.079	2.008	19907.440	.010%	99.882%
115.0	4.746	2.235	19909.680	.011%	99.894%
120.0	5.276	2.436	19912.110	.012%	99.906%
125.0	5.779	2.555	19914.670	.013%	99.919%
130.0	6.119	2.587	19917.250	.013%	99.932%
135.0	6.187	2.487	19919.740	.012%	99.944%
140.0	6.173	2.289	19922.030	.011%	99.956%
145.0	6.187	2.062	19924.090	.010%	99.966%
150.0	6.269	1.834	19925.930	.009%	99.975%
155.0	6.106	1.566	19927.490	.008%	99.983%
160.0	5.820	1.251	19928.740	.006%	99.989%
165.0	5.684	.948	19929.690	.005%	99.994%
170.0	5.480	.662	19930.350	.003%	99.997%
175.0	5.453	.391	19930.740	.002%	99.999%
180.0	5.657	.133	19930.880	.001%	100.000%




Luminous Intensity Distribution Diagram

Light Distribution Curve [Unit:cd]





Lux distance Curve



Max , Ave

Beam angle of C180plane154.04

**Luminous Intensity Distribution Data**

C/γ(°)	0.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0
0.0	4086.26	4064.50	4110.19	4158.05	4234.20	4358.21	4497.45	4601.88	4691.08
22.5	4036.22	4081.91	4153.70	4288.59	4451.76	4669.33	4930.40	5248.04	5565.68
45.0	3986.18	4097.14	4262.48	4453.94	4693.26	4984.79	5261.10	5556.98	5800.65
67.5	3960.07	4116.72	4371.27	4623.64	4886.89	5147.96	5385.11	5541.75	5641.83
90.0	3901.33	4140.65	4480.05	4765.05	4976.09	5221.94	5454.73	5604.85	5724.50
112.5	3940.49	4136.30	4399.55	4673.68	4980.44	5250.22	5509.12	5737.56	5946.42
135.0	3947.02	4108.02	4338.63	4580.13	4880.36	5219.76	5598.32	6048.67	6409.83
157.5	3957.90	4060.15	4205.92	4414.78	4669.33	4969.56	5304.61	5752.79	6290.17
180.0	4086.26	4171.11	4258.13	4382.14	4547.49	4762.88	4880.36	5110.98	5367.70
202.5	4036.22	4038.40	4029.69	4099.31	4192.86	4301.65	4419.13	4577.95	4754.18
225.0	3986.18	3938.32	3940.49	3964.42	4029.69	4057.98	4084.08	4118.89	4003.59
247.5	3960.07	3901.33	3849.12	3851.29	3868.70	3907.86	3953.55	3866.52	3411.82
270.0	3901.33	3809.95	3805.60	3807.78	3807.78	3801.25	3840.41	3668.54	3142.04
292.5	3940.49	3838.24	3807.78	3775.14	3764.27	3790.37	3853.47	3788.20	3344.37
315.0	3947.02	3862.17	3836.06	3833.89	3851.29	3899.16	3931.79	3944.84	3829.54
337.5	3957.90	3901.33	3868.70	3883.93	3942.67	3986.18	4001.41	4053.63	4203.74
360.0	4086.26	4064.50	4110.19	4158.05	4234.20	4358.21	4497.45	4601.88	4691.08

C/γ(°)	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
0.0	4960.86	5328.54	6026.92	6790.56	7147.36	5659.24	2432.78	432.51	94.21
22.5	5926.84	6259.71	6462.04	6499.03	6314.10	5680.99	3318.05	1453.75	217.35
45.0	6018.21	6153.10	6094.36	5861.57	5352.47	4337.76	2790.89	501.70	138.59
67.5	5720.15	5724.50	5498.24	4882.54	3698.35	2112.53	893.09	222.78	110.96
90.0	5822.41	5800.65	5363.35	4334.93	2811.56	1227.71	289.14	169.26	91.16
112.5	6103.06	6061.73	5800.65	5069.64	3951.37	2354.03	1074.32	241.28	114.00
135.0	6599.11	6586.05	6457.69	6170.51	5704.92	5071.82	2947.32	664.65	135.76
157.5	6705.71	6951.56	6977.66	6840.60	6573.00	5715.80	3480.57	1556.44	179.05
180.0	5726.68	6385.90	7173.47	7889.25	7906.66	6131.35	3431.40	1129.58	117.27
202.5	4943.46	4917.35	4353.86	3333.49	3159.44	3809.95	1123.06	427.08	285.66
225.0	3490.14	2641.64	2004.19	1747.46	706.21	537.16	405.32	244.54	69.84
247.5	2602.48	1891.05	1573.41	804.76	531.29	405.75	247.37	129.23	62.01
270.0	2293.54	1740.94	1442.88	644.64	425.55	264.12	176.01	105.74	50.69
292.5	2537.21	1845.37	1601.70	776.26	509.75	368.55	223.65	114.87	57.65
315.0	3305.21	2393.62	1814.91	1638.68	620.71	499.74	371.81	218.00	69.62
337.5	4362.56	4312.52	3725.11	2713.44	2691.68	3118.11	1120.88	367.25	213.65
360.0	4960.86	5328.54	6026.92	6790.56	7147.36	5659.24	2432.78	432.51	94.21

C/γ(°)	90.0	95.0	100.0	105.0	110.0	115.0	120.0	125.0	130.0
0.0	7.40	3.92	3.70	3.92	4.35	5.00	5.22	5.44	5.87
22.5	31.11	4.13	3.48	3.05	3.26	3.48	4.13	4.57	5.00
45.0	34.59	3.92	2.83	2.39	2.18	2.39	2.83	3.48	3.92
67.5	38.73	3.05	2.18	1.74	1.74	1.96	2.39	3.05	3.70
90.0	22.19	2.61	1.74	1.52	1.74	2.18	2.61	2.83	3.70
112.5	38.29	2.39	1.96	1.74	1.96	2.39	3.05	3.48	4.13
135.0	33.29	3.26	2.83	2.83	3.05	3.70	4.35	4.79	5.22
157.5	34.38	4.79	4.35	4.79	5.22	6.09	6.31	6.53	6.31
180.0	15.45	4.13	4.13	3.70	3.92	4.79	5.22	5.44	5.66
202.5	12.18	4.13	4.35	5.22	6.09	6.74	7.18	7.40	7.40
225.0	5.22	3.26	4.13	5.44	6.31	6.96	7.62	8.05	7.83
247.5	2.39	2.61	3.26	4.13	5.44	6.31	6.74	7.40	7.62
270.0	2.18	1.96	2.61	3.48	4.35	5.66	6.31	6.96	7.40
292.5	2.18	2.61	2.83	3.48	4.13	5.00	6.09	6.96	7.62
315.0	5.44	3.48	3.70	4.57	5.22	6.09	6.74	7.62	8.27
337.5	9.79	5.00	5.22	5.66	6.31	7.18	7.62	8.49	8.27
360.0	7.40	3.92	3.70	3.92	4.35	5.00	5.22	5.44	5.87



C/γ(°)	135.0	140.0	145.0	150.0	155.0	160.0	165.0	170.0	175.0
0.0	5.66	5.44	5.22	5.22	4.79	4.57	4.35	4.35	4.13
22.5	5.22	5.22	5.44	5.87	5.87	5.66	5.44	5.44	5.66
45.0	4.35	4.79	5.22	5.44	5.44	5.44	5.44	5.66	5.44
67.5	3.92	4.35	4.79	5.22	5.22	5.44	5.66	5.44	5.44
90.0	3.92	4.57	5.00	5.44	5.44	5.44	5.66	5.44	5.66
112.5	4.35	5.00	5.22	5.66	5.44	5.44	5.66	5.44	5.66
135.0	5.66	5.44	5.66	5.66	5.66	5.66	5.66	5.44	5.66
157.5	6.31	6.31	6.09	6.31	6.09	5.66	5.87	5.44	5.87
180.0	5.66	5.44	5.44	5.66	5.66	5.44	5.22	5.00	5.22
202.5	6.96	6.74	6.31	6.31	6.09	5.87	5.44	5.44	5.00
225.0	7.62	6.96	6.96	6.53	6.53	5.87	5.87	5.44	5.44
247.5	7.83	7.40	7.18	7.18	6.74	6.31	5.66	5.66	5.44
270.0	7.83	7.62	7.62	7.18	7.18	6.31	6.09	5.66	5.44
292.5	7.62	7.62	7.40	7.62	7.18	6.74	6.31	5.87	5.66
315.0	7.83	7.83	7.62	7.62	7.18	6.53	6.31	6.09	5.66
337.5	8.27	8.05	7.83	7.40	7.18	6.74	6.31	5.87	5.87
360.0	5.66	5.44	5.22	5.22	4.79	4.57	4.35	4.35	4.13

C/γ(°)	180.0
0.0	4.35
22.5	5.66
45.0	5.66
67.5	5.87
90.0	5.87
112.5	5.87
135.0	5.87
157.5	6.09
180.0	4.35
202.5	5.66
225.0	5.66
247.5	5.87
270.0	5.87
292.5	5.87
315.0	5.87
337.5	6.09
360.0	4.35



5 Performance Assessment

Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
IK-SBSL2-L130-0150A-3000K	3000K	20168.33	155.74	129.5
IK-SBSL2-L130-0150A-3500K	3500K	20565.09 ^{*1}	154.42 ^{*2}	133.2 ^{*3}
IK-SBSL2-L130-0150A-4000K	4000K	20961.85 ^{*1}	154.42 ^{*2}	135.8 ^{*3}
IK-SBSL2-L130-0150A-4500K	4500K	21358.60 ^{*1}	154.42 ^{*2}	138.3 ^{*3}
IK-SBSL2-L130-0150A-5000K	5000K	21755.36 ^{*1}	154.42 ^{*2}	140.9 ^{*3}
IK-SBSL2-L130-0150A-5700K	5700K	22152.12	153.09	144.7

*1: This value is calculated and the calculation formula is as below:

$$20565.09 = (22152.12 - 20168.33) / 5 + 20168.33$$

$$20961.85 = (22152.12 - 20168.33) / 5 + 20565.09$$

$$21358.60 = (22152.12 - 20168.33) / 5 + 20961.85$$

$$21755.36 = (22152.12 - 20168.33) / 5 + 21358.60$$

*2: This value is calculated and the calculation formula is as below:

$$154.42 = (155.74 + 153.09) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$133.2 = 20565.09 / 154.42$$

$$135.8 = 20961.85 / 154.42$$

$$138.3 = 21358.60 / 154.42$$

$$140.9 = 21755.36 / 154.42$$



Photo Document



****End of test report****