



Not all product variations listed on this page are DLC qualified. Visit <https://www.designlights.org/qpl> to confirm qualification.

LOCUS GEN2

AREA LUMINAIRE (POWER SELECTABLE)

IKIO's Locus Gen2 Area Luminaire combines architectural form and versatility to make an excellent lighting solution for new construction or retrofit applications. Its power selectable capability, when added to features like custom-engineered optics, dimming options, and high-output LEDs, delivers the highest levels of convenience to users while resulting in clear, uniform illumination and lasting performance. It is designed to replace the existing HID fixtures up to 1000 W.

Applications: Outdoor Illumination Needs, Including Parking Lots, Auto Dealerships, Pathways, Roadways, Recreational Venues, and Other General Area Lighting (Can Also be Used as Flood Lights).

FEATURES

- Increased flexibility and ease with IKIO's **Power Selectable (switch between 75-100-150-200-240-300 W)** feature.
- **Sleek, low-profile design** that delivers high-performance illumination and improves application site aesthetics.
- **Heavy-duty, die-cast aluminum housing** with an efficient heat sink for enhanced thermal performance.
- **Designed for Dark Sky compliant performance** to eliminate undesirable sky glow.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

LOCUS GEN2 AREA LUMINAIRE - 0-10 V DIMMING - 100-277 V FIXTURES

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187540092	LOCUS GEN2 AL: 154.4 W / 11902.5-15970-24495 LM / 5000 K / 100-277 V / BRONZE	•	158.7 lm/W	400 W	View / Download
662187487984	LOCUS GEN2 AL: 154.4 W / 11902.5-15970-24495 LM / 5000 K / 100-277 V / WHITE	•	158.7 lm/W	400 W	View / Download
662187487991	LOCUS GEN2 AL: 302.5 W / 32240-38688-48780 LM / 5000 K / 100-277 V / BRONZE	•	161.2 lm/W	1000 W	View / Download
662187488004	LOCUS GEN2 AL: 302.5 W / 32240-38688-48780 LM / 5000 K / 100-277 V / WHITE	•	161.2 lm/W	1000 W	View / Download

LOCUS GEN2 AREA LUMINAIRE - 0-10 V DIMMING - 277-480 V FIXTURES

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187540085	LOCUS GEN2 AL: 150.8 W / 12202.5-16270-24527 LM / 5000 K / 277-480 V / BRONZE	•	162.7 lm/W	400 W	View / Download
662187540078	LOCUS GEN2 AL: 150.8 W / 12202.5-16270-24527 LM / 5000 K / 277-480 V / WHITE	•	162.7 lm/W	400 W	View / Download
662187540061	LOCUS GEN2 AL: 300.7 W / 33020-39624-49626 LM / 5000 K / 277-480 V / BRONZE	•	165.1 lm/W	1000 W	View / Download
662187540054	LOCUS GEN2 AL: 300.7 W / 33020-39624-49626 LM / 5000 K / 277-480 V / WHITE	•	165.1 lm/W	1000 W	View / Download

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187560120	IK-SBSL/2-S4C-90-480V	SHORTING CAP	View / Download
662187560021	IK-SBSL/2-PHC-90-277V	PHOTOCELL 90-277 V	View / Download
662187560106	IK-SBSL/2-PHC-200-480V	PHOTOCELL 277-480 V	View / Download
662187549910	IK-SBSL1-SF-A (Bronze)	ARM MOUNTING BRACKET: A - SLIP FITTER (BRONZE)	View / Download
662187549941	IK-SBSL1-SP-B (Bronze)	POLE MOUNTING BRACKET: B - SQUARE & ROUND (BRONZE)	View / Download
662187549972	IK-SBSL1-TR-C (Bronze)	WALL MOUNTING BRACKET: C - TRUNNION (BRONZE)	View / Download
662187548470	IK-SBSL1-SP-B-(Spacer) Bronze	SPACER (BRONZE)	-
662187549934	IK-SBSL1-SF-A (White)	ARM MOUNTING BRACKET: A - SLIP FITTER (WHITE)	View / Download
662187549965	IK-SBSL1-SP-B (White)	POLE MOUNTING BRACKET: B - SQUARE & ROUND (WHITE)	View / Download
662187549996	IK-SBSL1-TR-C (White)	WALL MOUNTING BRACKET: C - TRUNNION (WHITE)	View / Download
662187481999	IK-SBSL1-SP-B-(Spacer) White	SPACER (WHITE)	-

*Choice of One Accessory: Mounting Bracket (Slip Fitter, Square & Round with Spacer, Trunnion Mount), Shorting Cap or Photocell (either one) is included with the order. Contact your IKIO sales representative to buy a replacement/additional Mounting Bracket.

*Product requires top-mounted shorting cap or optional twist-lock photocell installed to operate.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

