Product Sheet





IKIO's Novus Architectural Flood Light is known for its unique design and extruded lamp body. This makes the luminaire an effective and lasting solution for general spaces like lawns, alleys, and pathways. With features like CCT & power selectability, a microwave motion sensor, and 125 lm/W lumen output, Novus provides greater flexibility and allows users to implement light as per their unique application needs. Choose Novus for even illumination and excellent lighting in your spaces.

Applications: Outdoor Illumination Needs, Including Parking Lots, Auto Dealerships, Pathways, Roadways, Recreational Venues, and Other General Areas; Can Also be Used as Flood Lights.

FEATURES

- CCT & power selectable functionality ensures flexibility in applications for users.
- High-efficacy luminaire (125 lm/W) with exceptional lumen output to light up the area right.
- Unique design with a strong, extruded lamp body.

- IP65 rating makes it suitable for wet locations.
- **Dimming capability** gives the user better control of the lighting.
- Solid aluminum housing with excellent heat dissipation.

PRODUCT ORDERING DETAILS

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	BEAM	TRAD. EQUIV	SPEC SHEET
662187478876	NOVUS AFL: 55 W / 1875-3750-6875 LM / 30-40-50 K / 120-277 V / BRONZE	٠	125 lm/W	30°	250 W	View / Download

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

